



BOLIY Pro3600Si DSP INVERTER GENERATOR

	
SPECIFICATIONS	Pro3600Si
OVERALL LENGTH (in)	23
OVERALL WIDTH (in)	16.5
OVERALL HEIGHT (in)	18.5
DRY WEIGHT (lbs)	68
GROSS WEIGHT (lbs)	75
FUEL TANK CAPACITY (US gal.)	1.6
NOISE LEVEL (1/4 load at 23 ft)	53-58dB
GENERATOR	
TYPE	AC OUTPUT, MULTISTAGE PERMANENT-MAGNET GENERATOR
RATED OUTPUT (WATTS)	3000
MAX OUTPUT (WATTS)	3300
FULL TANK OUTPUT (WATTS)	13500
RUN TIME AT 1/2 RATED LOAD	7.5hours
RUN TIME AT RATED LOAD	4hours
RATED VOLTAGE (V)	120V North America / 230V Europe
FREQUENCY (Hz)	60Hz North America / 50Hz Europe
RATED CURRENT (A)	19.2 (A) North America / 10 (A) Europe
DC OUTPUT (12V/8A)	YES
ENGINE	
TYPE	166F, OHV, AIR-COOLED, 4- STROKE
STARTING SYSTEM	RECOIL START
CYLINDER ARRANGEMENT	INCLINED, SINGLE CYLINDER
BORE x STROKE (mm/in)	66(2.6)×50(1.97)
IGNITION SYSTEM	CDI
SPARK PLUG TYPE	BPR4 ES(NGK)/F7RTC
GAP (mm/in)	0.7-0.8(0.028-0.031)
DISPLACEMENT	171CC
RATED OUTPUT (HP r/min)	4.9/3600
FUEL	UNLEADED GASOLINE
ENGINE OIL QUANTITY (US qt)	0.63
THE FLUCTUATION OF VOLTAGE & FREQUENCY	
INSTANTANEOUS	25%
STABLE STATE	0%
STABLE TIME (second)	3
FREQUENCY	0.2%
CHARACTERISTIC	
AUTOMATIC RELEASE PRESSURE	YES
ELECTRO-BREAKER	YES
FUEL LEVEL GAUGE	YES
ENGINE OIL WARNING LIGHT	YES
OVERLOAD INDICATOR LIGHT	NO
AC INDICATOR LIGHT	YES
ENERGY CONSERVATION CURRENT IDLING	YES
INSULATION CLASS	F